

## SERVICE CARTS - OFFSET HANDLE LOW PROFILE (2 SHELVES)

**Model SL - Low flush top shelf for shorter lift of heavier items.**



**1,200 LB CAP.\***  
 (\*800 lb with Thermorubber casters)



### OPTIONS

- 2 wheel brakes on swivel casters - Code B5
- All swivel casters - Code AS
- Floor lock - Code F5
- Bottom shelf lips down (flush) - Code FB
- Top shelf lips up - Code GT
- Locking drawer 5"h x 16"w x 20"d with 2 keys - Code DS
- Vinyl matting on top shelf - Code VM
- Larger casters (page 123) and other shelf heights available.

### FEATURES

All welded construction (except casters), with durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.

Raised offset handle (12" above top shelf).

Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.

1-1/2" shelf lips down (flush) on top shelf and lips up on bottom shelf (see options).

Clearance between shelves - 17" - Top shelf height - 27" (see options).

| WxL<br>(IN) | 5" CASTERS CAT. NO.'S |              |          | WGT.<br>(LBS) |
|-------------|-----------------------|--------------|----------|---------------|
|             | URETHANE              | THERMORUBBER | STEEL    |               |
| 18 X 24     | SL124-U5              | SL124-T5     | SL124-L5 | 72            |
| 30          | SL130-U5              | SL130-T5     | SL130-L5 | 80            |
| 36          | SL136-U5              | SL136-T5     | SL136-L5 | 88            |
| 48          | SL148-U5              | SL148-T5     | SL148-L5 | 102           |
| 24 X 24     | SL224-U5              | SL224-T5     | SL224-L5 | 86            |
| 30          | SL230-U5              | SL230-T5     | SL230-L5 | 96            |
| 36          | SL236-U5              | SL236-T5     | SL236-L5 | 106           |
| 42          | SL242-U5              | SL242-T5     | SL242-L5 | 116           |
| 48          | SL248-U5              | SL248-T5     | SL248-L5 | 126           |
| 60          | SL260-U5              | SL260-T5     | SL260-L5 | 146           |
| 72          | SL272-U5              | SL272-T5     | SL272-L5 | 166           |
| 30 X 36     | SL336-U5              | SL336-T5     | SL336-L5 | 122           |
| 48          | SL348-U5              | SL348-T5     | SL348-L5 | 148           |
| 60          | SL360-U5              | SL360-T5     | SL360-L5 | 174           |
| 72          | SL372-U5              | SL372-T5     | SL372-L5 | 198           |
| 36 X 48     | SL448-U5              | SL448-T5     | SL448-L5 | 170           |
| 60          | SL460-U5              | SL460-T5     | SL460-L5 | 200           |
| 72          | SL472-U5              | SL472-T5     | SL472-L5 | 230           |

## OFFSET HANDLE LOW PROFILE (PNEUMATIC CASTERS) (2 SHELVES)

**Model SS - Low flush top shelf vibration reduction transporter.**



**1,200 LB CAPACITY**



### OPTIONS

- 2 wheel brakes on swivel casters - Code BN
- All swivel casters - Code AS
- Floor lock - Code FN
- Top shelf lips up - Code GT
- Bottom shelf lips down (flush) - Code FB
- Locking drawer 5"h x 16"w x 20"d with 2 keys - Code DS
- Vinyl matting on top shelf - Code VM
- Other shelf heights available

### FEATURES

All welded construction (except casters), with durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.

Raised offset handle (12" above top shelf).

Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - Semi or full pneumatic casters

1-1/2" shelf lips down (flush) on top shelf and lips up on bottom shelf (see options).

Clearance between shelves - 17".

Top shelf height - 31" (8" casters).

| WxL<br>(IN) | PNEUMATIC CASTERS |               | WGT.(LBS) |
|-------------|-------------------|---------------|-----------|
|             | SEMI CAT. NO.     | FULL CAT. NO. |           |
| 24 X 30     | SS230-Z8          | SS230-N8      | 120       |
| 36          | SS236-Z8          | SS236-N8      | 130       |
| 42          | SS242-Z8          | SS242-N8      | 142       |
| 48          | SS248-Z8          | SS248-N8      | 152       |
| 60          | SS260-Z8          | SS260-N8      | 172       |
| 72          | SS272-Z8          | SS272-N8      | 192       |
| 30 X 36     | SS336-Z8          | SS336-N8      | 148       |
| 48          | SS348-Z8          | SS348-N8      | 174       |
| 60          | SS360-Z8          | SS360-N8      | 198       |
| 72          | SS372-Z8          | SS372-N8      | 222       |
| 36 X 48     | SS448-Z8          | SS448-N8      | 196       |
| 60          | SS460-Z8          | SS460-N8      | 224       |
| 72          | SS472-Z8          | SS472-N8      | 254       |

