

SENTRY STORED PRESSURE DRY CHEMICAL FIRE EXTINGUISHERS



FEATURES

- ULC Listed
- ABC multi-purpose (ammonium phosphate) or PDC standard (sodium bicarbonate) dry chemical
- Easy -to-service (internal spring) valve
- Squeeze grip with positive on/off operation
- Suitable for use in temperatures from -65° F to 120° F (-54° C to 49° C)
- Clear anodized aluminum valve
- Units supplied with wall hanging bracket
- 2-1/2 and 5 lb. units also available with vehicle bracket
- Heavy-duty running board bracket available for 10-30 lbs. units (sold separately)
- Six-year limited warranty



SPECIFICATIONS

	MODEL NO.	ULC RATING	EFFECTIVE RANGE (FT / M)	CAPACITY LBS / KG	DISCHARGE TIME (SEC)	DIAMETER IN / CM	WIDTH IN / CM	HEIGHT IN / CM
ABC	AA25V	1-A:10-B:C	8-10 / 2.4-3.0	2.5 / 1.1	8-10	3 / 7.6	4.5 / 11.4	16 / 40.6
	AA05W	3-A:10-B:C	10-15 / 3.0-4.6	5 / 2.3	13-15	4.25 / 10.8	5.5 / 14.0	16.5 / 41.9
	AA05V	3-A:10-B:C	10-15 / 3.0-4.6	5 / 2.3	13-15	4.25 / 10.8	5.5 / 14.0	16.5 / 41.9
	AA05W340	3-A:40-B:C	10-15 / 3.0-4.6	5 / 2.3	13-15	4.25 / 10.8	5.5 / 14.0	17.8 / 45.2
	AA05V340	3-A:40-B:C	10-15 / 3.0-4.6	5 / 2.3	13-15	4.25 / 10.8	5.5 / 14.0	17.8 / 45.2
BC	AA10S	4-A:60-B:C	10-15 / 3.0-4.6	10 / 4.5	20-22	5.5 / 14.0	9 / 22.9	20 / 50.8
	AA20	4-A:60-B:C	12-18 / 3.7-5.5	20 / 9.1	26-30	7 / 17.8	10 / 25.4	24 / 61.0
	C10S	60-B:C	10-15 / 3.0-4.6	10 / 4.5	17-20	5.5 / 14.0	9 / 22.9	20 / 50.8
	C20	120-B:C	12-18 / 3.7-5.5	20 / 12.2	26-30	7 / 17.8	10 / 25.4	24 / 61.0
K	PK10S	80-B:C	10-15 / 3.0-4.6	10 / 4.5	20-22	5.5 / 14.0	9 / 22.9	20 / 50.8
	PK20	120-B:C	12-18 / 3.7-5.5	20 / 9.1	26-30	7 / 17.8	10 / 25.4	24 / 61.0
A	K-GUARD	2-K	8-10 / 2.4-3.0	6 L (1.59 GAL)	54	7 / 17.8	9.5 / 24.1	21.25 / 54.0
	APW	2A	44-55 / 13-16		60	7 / 17.8	8 / 20.3	25.5 / 64.8

