

Gas-Cylinder Process Stations

Provides secure gas-cylinder storage and easy-to-reach control mounting panels for gas distribution

- Fully welded construction using 11-gauge (3-mm) steel provides structural integrity and longevity
- Securely mount cylinder controls and cross-over devices with integral elevated panels or dual mounting struts

Designed for the safe storage and distribution of industrial and commercial use compressed gas cylinders, these storage stands help prevent dangerous tipping situations. Store cylinders from 4- to 12-in (102- to 305-mm) in diameter. Steel stands are powder-coated to ensure long service life and chemical resistance. Exclusive bumper guard edging with steel reinforced vinyl protects your cylinders from damage while providing extra grip. Pre-drilled holes in base designed for floor mounting with application specific fasteners (not included).

Heavy-duty polypropylene support straps, 1.5-in (38-mm) wide and rated at 1138-lb (516-kg), feature steel cinch buckle and hold individual cylinders securely against integral bracket to prevent tipping. Stainless steel models use a nylon side latch buckle to protect against corrosion. For an improved level of safety on any installation, most stands include openings to retrofit secondary support chains, one set for each cylinder station. Add **model 35366** to get an optional steel chain for your stand bracket. One chain for each cylinder strap. Welded and plated, heavy-duty size 2/0 steel chains with twist link allows links to lay flat against the cylinders, enabling a tighter fit and preventing damage to required labeling.



Process rack model 35314 accepts three cylinders on each side. Add cylinder controls or cross-over devices on top panel for safe gas distribution.



35306



35310



35304

Custom Designed Process Control Station



Before



After

Photos courtesy of Praxair Specialty Gases

Gas-Cylinder Process Stands

Cylinder Capacity	Max Cylinder Diameter in/mm	Mount Type/Orientation	Control Mount Type	Nominal Dimensions H x W x D	Straps Per Cylinder	Approv/Lstg Regulation	Model No	Ship Wt lb/kg
1	12/305	Floor	Panel	72 x 18 x 13.75 in 1829 x 457 x 349 mm	2	O, C, G, A	35304	117/53
2	12/305	Floor	Panel	72 x 28 x 10.5 in 1829 x 705 x 267 mm	1		35306	61/28
3	12/305	Floor	Panel	72 x 40 x 10.5 in 1829 x 1016 x 267 mm	1		35308	84/38
4	12/305	Floor	Dual Struts	72 x 52 x 14 in 1829 x 1321 x 356 mm	2		35310	155/70
4	12/305	Floor Back to Back	Panel	72 x 32 x 23 in 1829 x 813 x 584 mm	2		35312	98/44
6	12/305	Floor Back to Back	Panel	72 x 44 x 23 in 1829 x 1118 x 584 mm	2		35314	129/59

Extra Accessories for Gas-Cylinder Process Stands

Description	Model No	Ship Wt lb/kg
Chain, one-piece, 41 in (1041 mm) long	35366	1/1

1 Year
Limited Warranty