



Type II AccuFlow™ Transport and Dispensing Cans

Provides D.O.T. compliant travel mode for over-the-road transport of flammable liquids and FM-approved usage mode for on-site fuel dispensing

- Heavy-duty roll-bars protect the spout from damage to prevent dangerous fuel spillage during transport
- Usage mode for on-site fuel dispensing
- Eliminates vapor release and spills when in travel mode by engaging the hold-down bracket with easy-to-grasp tightening screw
- Bracket tethered to spout features a fusible link that melts at 165 F (74 C) to prevent pressure build-up at elevated temperatures
- Patented AccuFlow™ manifold includes air displacement vent for smooth, glug-free liquid flow
- Easy-to-use flow-control Safe-Squeeze® trigger provides fast, precision pouring
- FM-approved and meets D.O.T. UN marking 1A1/Y1.2/100



Description and Capacity	Hose OD x L (mm)	Can OD x H (mm)	Approv/Lstg Regulation	D.O.T. Red Model	D.O.T. Yellow Model	CA Prop 65
2.5 gallon (9.5L) D.O.T. Type II can	0.625 x 9 in (16 x 229 mm)	11.75 x 13 in (298 x 330 mm)	FM, D.O.T., UN	7325120	7325220	⚠
2.5 gallon (9.5L) D.O.T. Type II can	1 x 9 in (25 x 229 mm)			7325130	7325230	⚠
5 gallon (19L) D.O.T. Type II can	0.625 x 9 in (16 x 229 mm)	11.75 x 18.5 in (298 x 470 mm)		7350110	7350210	⚠
5 gallon (19L) D.O.T. Type II can	1 x 9 in (25 x 229 mm)			7350130	7350230	⚠

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.