

## Oily Waste Cans

Dispose of oil-soaked rags and prevent fires caused by stray sparks or spontaneous combustion

- Lid stays closed when not in use to isolate contents from fire sources and limit available oxygen
- Round construction and elevated base allow circulation of air around can to disperse heat and reduce moisture build-up and rusting
- Durable steel construction with a powder-coat finish provides chemical resistance
- Swinging carry handle for portability
- Warning label with pictographs reduces miscommunication
- FM-approved; meets OSHA requirements



Foot pedal provides hands-free opening. When released, cover self-closes to reduce oxygen source and prevent a fire from starting.



Description and Nominal Gallon Capacity	OD x H	Approv/Lstg Regulation	Red Model	
			Foot-Operated	Hand-Operated*
0.45 gallon (2 L) oily waste can	7 x 10.5 in (178 x 267 mm)	FM, NESAM, EPA	—	09400
2 gallon (8 L) oily waste can	9.625 x 9.125 in (244 x 232 mm)	FM	—	09200
6 gallon (20 L) oily waste can	11.875 x 15.875 in (302 x 403 mm)	FM, UL, TÜV	09100	09110
10 gallon (34 L) oily waste can	13.938 x 18.25 in (354 x 464 mm)		09300	09310
14 gallon (52 L) oily waste can	16.063 x 20.25 in (408 x 514 mm)		09500	09510
21 gallon (80 L) oily waste can	18.375 x 23.438 in (467 x 595 mm)		09700	09710

\*Hand-operated models do not have TÜV certification.