



FEATURES

100% VIRGIN
POLYESTER SINGLE
JACKET, TWILL WEAVE
POLYURETHANE (PU)
TUBE

PACKAGE

FOLDED, PACKED IN CARTON OF 2

APPLICATION

INTERIOR FIRE PROTECTION
RACK HOSE IS AN INTEGRAL
PART OF THE BASE BUILDING
STANDPIPE FIRE PROTECTION SYSTEMS.

SOFTFLEX Single Jacket Rack Hose



SOFTFLEX rack hose is designed for quick and easy installation & annual refolding. Our hose is soft and flexible with a PU lining designed to stand up to multiple hydrostatic tests. Our couplings are all hydro tested after installation as per NFPA 1962 requirements to assure quality and performance.

MODEL	PRODUCT DESCRIPTION	HOSE DIAMETER (INCH / MM)	SERVICE PRESSURE (PSI / BAR)	MINIMUM BURST PRESSURE (PSI / BAR)
RH-50	50' w/ Brass Couplings	1.5"/ 38	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
RH-75	75' w/ Brass Couplings	1.5"/ 38	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
RH-100	100' w/ Brass Couplings	1.5"/ 38	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC

*Standard lengths: 15m (50ft), 22.5m (75ft), 30m (100ft), also can be customized according to requirements. Also available in CHROME POLISHED Coupling. -CHR**